Bann Special

Materials:

Hook:	Partridge CS14 #7-15
Thread:	Black 8/0
Tag:	Twisted silver wire
Tail:	Gold Pheasant red breast feathers wound
Rear body:	Yellow floss or UNISTRETCH
Ribbing:	Twisted silver wire
Centre Hackle:	Hot orange cock
Front body:	black floss or UNISTRETCH
Wings:	Jungle cock (roofed)
Front Hackle:	Silver badger Cock
Plus:	UV glue or black head cement






Tie in the thread at the eye of the hook and wind it in close turns to the beginning of the curvature of the hook



- For the tag, wind the twisted wire backwards into direction of the curvature of the hook for 5 6 turns
- 4 Bring the wire from above the hook shank under the hook shank, passing it between the 2 hooks
- 5 Tie off the wire in front of the tag and flip it back between the 2 hooks



Tie in the twisted silver wire



6 Tie in a GP red breast feather by the tip of the feather



- Wind 2 turns with the GP feather
- 8 Tie it off
- Overwind the feather tips with the tying thread exactly to the beginning of the tag
- of the tag

 10 Wind the thread to the middle of the hook shank



- 12 Wind the UNISTRETCH to the beginning of the tag and then back to the middle of the hook shank
- 13 Tie off the UNISTRETCH



- 16 Tie in the orange cock feather by the tip
- 17 Wind 2 turns of wet hackle



11 Tie in the yellow UNISTRETCH



- 14 Wind the ribbing wire to the middle of the hook shank
- 15 Tie it off



18 Flip back the ribbing wire



Wind the tying thread to the eye of the hook

20 Tie in the black UNISTRETCH



23 Flip the silver wire in direction of the eye of the hook

Wind the ribbing of the front part of the body with the silver wire

Tie off the ribbing wire



Tie in the silver badger cock feather with its tip



Wind the UNISTRETCH to the beginning of the center hackle and then back to the eye of the hook

22 Tie off the UNISTRETCH



26 Tie in 2 jungle cock feathers as a wing (roofed)



Wind 2 turns of wet hackle 28 29 Tie off the silver badger cock feather



30 Wind the head of the fly 31 Whipfinish

- 32 Cut off the thread



Apply a drop of black head cement (or UV glue) on the head